



COMPRESSION LATCH STAINLESS STEEL 22 MM

Quarter-turn compression latch. Available both with clockwise or counter clockwise action to open. Close and tighten with a single continuous half-turn motion. First 90° turn moves the cam 90°, the second 90° turn retracts the cam 6 mm. Protection degree IP66 and classed waterproof according to NEMA 4. The latch is supplied assembled and with screw with mechanical thread lock.



MATERIAL

Cam: Stainless steel 304
Housing: Stainless steel 316
Insert: Stainless steel 316
Nut: Stainless steel 304
Screw: Stainless steel 304

RELATED PRODUCTS

Similar products: 2-135, 2-136, 6-135, 6-136
Cams: 2-481
 Use the Index Code at industrilas.com

TECHNICAL INFORMATION

Cutout: COMBI
Standards: IP66, NEMA 4, DIN EN 61373
Torque:

Industrilas
 ——— When access counts ———

Make your selections in each column to create your article number (AABBCC-DEFF-HHLL)

AA Description	BB Material	CC Cam type	D Opening rotation	E Nut	FF Insert	HHLL H/L in mm
24 Compression latch	90 SS 316	77 Fixed cam position	2 Counter-clockwise 3 Clock-wise	0 Standard nut	09 Square 8	0000 No cam
						0845 8 / 45
						1045 10 / 45
						1245 12 / 45
						1445 14 / 45
						1645 16 / 45
						1845 18 / 45
						2045 20 / 45
						2245 22 / 45
						2445 24 / 45
						2645 26 / 45
						2845 28 / 45
						3045 30 / 45
						3245 32 / 45
						3445 34 / 45
						3645 36 / 45
						3845 38 / 45
						4045 40 / 45
						4245 42 / 45
						4445 44 / 45
4645 46 / 45						
4845 48 / 45						
5045 50 / 45						
5245 52 / 45						
5445 54 / 45						