



Data subject to change without notice. Always confirm the data is correct from the seller.

KL1X16

Terminal Blocks

- **UL listed connectors, see link below**
- Sales unit = 1 piece
- Bi-metal terminal suitable for Al (KL terminals) / Cu (KL and KC terminals) cables
- Available in grey, blue (N) and yellow/green (PE)
- Touchproof, IP20
- Housing and cover in polyamide
- KL range: Certified according to IEC 61238-1 Class A
- KL range: Certified according to IEC 60947-7-1
- Terminal material KL tin-coated, greased aluminium
- Terminal material KC steel and brass
- KC-terminals and KL1X16 models for DIN-rail mounting, refer to detailed product specifications
- KL-terminals (excl. KL1X16 models) for DIN-rail or base mounting, refer to detailed product specifications
- Environmentally friendly materials
- Durable laser markings
- More information and package sizes from the catalogue
- **KLTS50 – 300** terminal shrouds available

Connector catalogue >>

Conductors per cross section (mm²) table >>

UL 1059 listed Terminal Blocks >>



Product details

| | |
|-----------------------------|---------------|
| SKU | KL1X16 |
| Al mm² | 1,5 - 16 |
| Color | L |
| Cu mm² | 1,5 - 16 |
| E-Number | 1942120 |
| EAN | 6419410484364 |
| In (Al) (A) | 75 |
| In (Cu) (A) | 76 |
| Key size | Hex 4 |
| Mounting | DIN |
| Number of Conductors | 2 |
| Package size | 60 |
| Torque Al/Cu (Nm) | 5 |
| Un (V) | 1000 |
| Weight (lb/kg) | 0.049 / 0.022 |

Dimensional drawing

