

Rated cross-section [mm ²):	120
Rated current [A] [A]	269
Short-time withstand current [A]	14 400
Rated voltage Ui [V]	1000
Rated impulse withstand voltage Uimp [V]	8000
Tightening torque [Nm]	3 (10 mm²)
Tightening torque [Nm]	6 (16 mm²)
Tightening torque [Nm]	10 (35 mm²)
Tightening torque [Nm]	25 (120 mm²)
Tool	Inbus
Assembly method	TH 35 / on the plate
IP code	20
Number of clamping points	12
Number of levels	1
End cover plate required	NO
Testing	EN 60947-7-1
Dimensions [mm] (width / height / length)	49 / 50 / 96
Weight [g]	400
Packing [pcs]	1

Conductor cross section

Conductor cross-section – Input [mm ²]	10 ÷ 120
Conductor cross-section – Output [mm ²]	2 x 6 ÷ 35
Conductor cross-section – Output [mm ²]	5 x 1,5 ÷ 25
Conductor cross-section – Output [mm ²]	4 x 1,5 ÷ 16
Stripping length (Input) [mm]	27 (120 mm²)
Stripping length (Output) [mm]	43 (35 mm²)
Stripping length (Output) [mm]	10 (16 mm² - top row)
Stripping length (Output) [mm]	36 (16 mm² - bottom row)
Délka odizolování vodiče [mm] (výstup)	20 (10 mm²)

