

Rated cross-section [mm <sup>2</sup> ):	<b>185</b>
Rated current [A] [A]	<b>400</b>
Short-time withstand current [A]	<b>22 200</b>
Rated voltage Ui [V]	<b>1000</b>
Rated impulse withstand voltage Uimp [V]	<b>8000</b>
Tightening torque [Nm]	<b>25 (185 mm<sup>2</sup>)</b>
Tightening torque [Nm]	<b>10 (35 mm<sup>2</sup>)</b>
Tightening torque [Nm]	<b>6 (16 mm<sup>2</sup>)</b>
Tightening torque [Nm]	<b>3 (10 mm<sup>2</sup>)</b>
Tool	<b>Inbus</b>
Assembly method	<b>TH 35 / on the plate</b>
IP code	<b>20</b>
Number of clamping points	<b>12</b>
Number of levels	<b>1</b>
End cover plate required	<b>NO</b>
Testing	<b>EN 60947-7-1</b>
Dimensions [mm] (width / height / length)	<b>49 / 50 / 96</b>
Weight [g]	<b>390</b>
Packing [pcs]	<b>1</b>

#### **Conductor cross section**

Conductor cross-section – Input [mm <sup>2</sup> ]	<b>70 ÷ 185</b>
Conductor cross-section – Output [mm <sup>2</sup> ]	<b>2 x 6 ÷ 35 (flexible wire with sleeve max. 25)</b>
Conductor cross-section – Output [mm <sup>2</sup> ]	<b>5 x 1,5 ÷ 25</b>
Conductor cross-section – Output [mm <sup>2</sup> ]	<b>4 x 1,5 ÷ 16</b>
Stripping length (Input) [mm]	<b>30 (185 mm<sup>2</sup>)</b>
Stripping length (Output) [mm]	<b>43 (35 mm<sup>2</sup>)</b>
Stripping length (Output) [mm]	<b>10 (16 mm<sup>2</sup> - top row)</b>
Stripping length (Output) [mm]	<b>36 (16 mm<sup>2</sup> - bottom row)</b>

