



Data subject to change without notice. Always confirm the data is correct from the seller.

# KU 3800CO

## LVK228LKX150

### KU Rotary switches and change-over switches 630-800A

- Made of halogen-free thermoplastic material. Materials have 100 % recyclability.
- Option for test position for testing auxiliary contacts while main contacts remain open. Note, only available on request.
- Reliable switch for demanding industrial applications
- Change-over switches: 'CO' included in type name
- Change-over switches with direct handle: 'CO SV' included in type name
- Change-over switches are always delivered with bridging bars
- Types without 'SV': Delivered with separate handle (**LKX 150**) and shaft (**LVK=228**)
- Available with yellow/red handle (**LKX 150 Y/R**) and a shaft of different length (100mm-500mm) on demand
- Types with 'SV': delivered with direct handle
- 800 A switch: AC-23 1000V 400 A
- Icw 690V (1s) 28kA
- R.M.S value 100kA
- Auxiliary contacts available (**1.V160KU** or **2.V160KU**), up to 8 NC / 8 NO
- Terminal covers and phase barriers (**VS800**) available
- Cable connectors for Al and Cu cables **available here**.

Technical Data

Accessories

Handle & Shaft

# KU Change-over Switches 10-800A



## Product details

<b>SKU</b>	KU 3800CO LVK228LKX150
<b>AC-21 400/415 V (A)</b>	800 A
<b>AC-21 690 V (A)</b>	800 A
<b>AC-22 400/415 V (A)</b>	800 A
<b>AC-22 690 V (A)</b>	800 A
<b>AC-23 400/415 V (A/kW)</b>	800 A / 400 kW
<b>AC-23 690 V (A/kW)</b>	800 A / 800 kW
<b>Cable Area to Switch Terminal (only Cu) (mm<sup>2</sup>) / Bolt size</b>	M12
<b>E-Number</b>	3602847
<b>EAN</b>	6419410483718
<b>Number of Poles</b>	3
<b>Operation</b>	Rotary
<b>Switch type</b>	Change-over Switch
<b>Weight (kg)</b>	8.985

## Dimensional drawing

