



RT 340

L42AD11LKX50

KU & RT Rotary switches 16-40A

- DIN-rail or screw mounting (KU) and door mounting (RT)
- 3-pole and 4-pole KU-switches as standard. 1 and 2-pole on request
- Switch technology by means of silver contacts ensures safe and durable operation
- Compatible (KU & RT) with handles LKX50, LKX50YR, LK10 and LK10YR
- Compatible (KU) with LXXXAD11 shafts (XXX is length of the shaft in millimetres)
- RT version is suitable for door mounting. Integrated aluminium shaft with AD11 adapter. Handle is required for door mounting installation. When using any other handle than LKX50, LKX50YR, LK10RT or LK10RTYR you will also need a special counter nut for the handle (**RT COUNTER NUT**)
- KU switch will be delivered with black direct handle. KU switches can also be used with external shaft and handle

Data subject to change without notice. Always confirm the data is correct from the seller.

Technical Data

Accessories

Handle & Shaft



Product details

SKU	RT 340 L42AD11LKX50
AC-21 400/415 V (A)	40 A
AC-21 690 V (A)	40 A
AC-22 400/415 V (A)	40 A
AC-22 690 V (A)	40 A
AC-23 400/415 V (A/kW)	40 A / 22 kW
AC-23 690 V (A/kW)	25 A / 22 kW
Cable Area to Switch Terminal (only Cu) (mm²) / Bolt size	1.5-16
EAN	6419410257777
Number of Poles	3
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	0.17

Dimensional drawing

